

LC-POWER

LC9450 V2.3

GOLD-Series



ATX V2.3 / EPS 12V

Due to its current ATX V2.3 standard, the LC9450 V2.3 power supply works perfectly in modern as well as in older computer systems.

Dual/Quad Core Support

The power supply supports all modern DualCore, QuadCore and server systems.

PCI-Express x 2

Includes two PCI-Express connectors (6/6+2) for graphic cards.

+12V Rail x 2

The power supply features two independent +12V rails (30 A/30 A) to provide stability and power for your system.

High Efficiency / 80 PLUS® GOLD certified

Modern technology decreases the standby mode power consumption and increases the efficiency of your power supply up to 90,36%.

Active PFC

Use active power factor correction (>0.99) to provide additional security to your system.

Advanced Security Circuitry

Over-Voltage Protection (OVP), Over-Current Protection (OCP), Over-Power Protection (OPP), Over-Temperature Protection (OTP), Under-Voltage Protection (UVP), Short-Circuit Protection (SCP)

135 mm Fan

Enjoy ultra silent work thanks to the high quality 135 mm fan.

Connectors:

1x 20+4 pin mainboard	50 cm
1x 4+4 pin mainboard 12V (8 pin EPS)	50 cm
1x PCI-Express V2.0 6+2 pin	65 cm
1x PCI-Express 6 pin	50 cm
4x SATA	2x 50/2x 65 cm
2x PATA	80 cm
1x FDD	adapter included in delivery

Barcode:	4260070123252
Mark of conformity:	TÜV, CE
Fan:	135 mm
PFC:	active
Weight (retail):	2,186 kg
Dimension:	86 x 150 x 158 mm (height x width x depth)

Power rating:	
+3,3V:	20A
+5V:	20A
max. combined:	100W

+12V1:	30A
+12V2:	30A
max. combined:	396W

max. combined:	400W
max. peak load:	450W